

The New Model 61202 Barometric Pressure Sensor offers unparalleled performance and flexibility for atmospheric pressure measurement. The barometer is available in two configurations to satisfy a variety of applications; Model 61202V offers 0-5 VDC output, 61202L offers a 4-20 mA current output. Both models offer serial output in addition to the analog signal.

The barometer is housed in a weatherproof molded case. Cable connections are inside. A U-bolt mounting is supplied for easy attachment to towers and masts. For outdoor installation, use of Model 61002 Pressure Port is recommended. The Pressure Port minimizes dynamic pressure errors due to wind.



Barometer and Pressure Port

Specifications

Operating Range:

600-1100 hPa (17.7 – 32.5 inHg)

Output Signal:

0-5 VDC (61202V)

4-20 mA (61202L)

Serial RS232/RS485 (all models)

Operating Temperature:

-50 to +60°C

Accuracy:

±0.3 hPa (.01 inHg) @ 20°C

±1.0 hPa (.03 inHg) over temperature range

Power Requirement:

10 to 30 VDC, 10 mA

Dimensions:

118mm (4.6 in) W x 73mm (2.8 in) H x 54 mm (2.1 in) D excluding mounting

Weight:

0.6 kg (1.3 lb)

Other:

Sea-level offset

Ordering Information

PRICE (US)

61202V	BAROMETRIC PRESSURE SENSOR, 0-5 VDC	\$650.00
61202L	BAROMETRIC PRESSURE SENSOR, 4-20 mA	\$650.00
61002	PRESSURE PORT WITH OFFSET BRACKET	\$126.00

Copyright © 2001 R.M. Young Company. Specifications subject to change without notice.



Complies with applicable CE Directives

Printed in U.S.A. 10/01



R.M. YOUNG COMPANY
2801 Aero Park Drive
Traverse City, Michigan 49686 U.S.A.
TEL: (231) 946-3980 FAX: (231) 946-4772
E-mail: met.sales@youngusa.com
Web Site: www.youngusa.com

Distributor in South Africa
Metron (PTY) LTD
89 Church Street
Hopefield, 7355, S.A
TEL: +27 (0)82 445 2531
TEL: +27 (0)83 427 6186
E-mail: itronics7@gmail.com
Web Site: www.inteltronics.co.za